

## Decorative Glass Wall Covering

### General Description

**Fibreglass wall covering** is used to cover walls and other interior surfaces. Product is perfect for new spaces: thanks to its high mechanical properties it prevents cracks from appearing, consequently prolonging the surface lifetime. It is also a performing solution for light renovation: it covers crack and wall irregularities.

Products from Novelio® Nature range are perfect solutions for easy application without important preparation of the wall surface and highly decorative expectations. This range mimics natural wall coverings and products don't need to be painted. Application is as simple as with wall papers

### Technical characteristics

| Technical Characteristics   |   |
|---|---|
| Composition   | 100 % coated glass fiber  |
| Treated fabric weight (average value)   | 185 g / m <sup>2</sup> (± 8 %)  |
| Loss on ignition (average value minimal)  | 29 %  |
| Oekotex certificate Standard 100  | Product Class III (does not contain any hazardous substance)  |
| Emission in indoor air  | A+ (very low)   |
| Fire resistance (EN 13501-1)  | Euroclass B, s1-d0 (A1, A2 board)   |
| Recommendation for application  |   |
| Quantity of vinyl glue  | 250 g / m <sup>2</sup> (approximate)  |
| Dimensions & Packaging  |   |
| Width (individual value)  | 49 cm / 98 cm (± 1 %)   |
| Roll length (individual value) <sup>(1)</sup>   | 10.05 m / 50 m (± 2 %)  |
| Repeat  | -   |
| Roll direction <sup>(1)</sup>   | Surface to apply on wall inside of roll   |
| Roll packaging <sup>(1)</sup>   | Collective box, wrapped into plastic foil   |
| Label on box <sup>(1)</sup>   | With installation instructions  |
| Storage conditions  | Dry room, storing temperature from -10°C to +50°C.<br>If product is not processed up to one week, it is not recommended to open a package or to remove a package from a roll. |
| Palette (non-returnable) <sup>(1)</sup>   | 1 box: 80 x 120 x 100 cm  |
| Quality Control   |   |
| Traceability  | Lot no. marked on the small sticker on the roll   |
| Defects marked by label   | Maximum 1 point defect / roll <sup>(1)</sup>  |
| Each defect is balanced by  | Adding 50 cm / defect <sup>(1)</sup>  |
| Product is carefully checked before leaving the factory but should also be checked just before applying. Any claim should be accompanied with roll sticker and a sample featuring the defect. |   |

(1) Details are described in works standard 0337

### Technical Data Sheet

#### Properties

- Wear-resistant wall covering
- High tensile strength
- Can be repainted
- Excellent Fire resistance
- Breathable
- Environmentally friendly
- Wet stability
- Invisible seams



Edited by:  
**ADFORS Construction Products Europe**

SAINT-GOBAIN ADFORS CZ s.r.o.  
Sokolovska 106  
CZ – 570 21 Litomyšl  
Tel: +420 461 651 111  
Fax: +420 461 612 769  
www.sg-adfors.com

**ADFORS Construction Products Europe** reserves the right to change the information given herein without prior notice

Technical Data Sheet N°1  
Last update: 20/08/2015