

Glass fiber Wall Covering

General Description

Glass fiber wall covering is used to cover walls and other interior surfaces. Product is perfect for new spaces: thanks to its high mechanical properties it prevents cracks from appearing, consequently prolonging the surface lifetime. It is also a performing solution for light renovation: it covers cracks and wall irregularities.

Products from Novelio® Nature range are perfect solutions for easy application without important preparation of the wall surface and highly decorative expectations. This range mimics natural wall coverings and products don't need to be painted.

Technical Characteristics

Technical Characteristics	
Composition	100 % coated glass fiber
Treated fabric weight (average value)	180 g/m ² (± 8 %)
Emission in indoor air	A+
Oekotex certificate standard 100	Class I
Fire resistance (EN 13501-1)	Euroclass B-s1,d0
Recommendation for application	
Quantity of glue	250 g/m ² (approximate)
Quantity of acrylic paint	
Dimensions & Packaging	
Width (individual value)	49 cm (± 1 % or closed pattern repeat)
Roll length (individual value) (1)	10.05 (± 1 %)
Paintable surface (2)	
Roll packaging (2)	Plastic foil
Label on roll (2)	With installation instructions
# rolls / pallet	192
Storage conditions	Dry room, storing temperature from -10 °C to +50 °C. If product is not processed up to one week, it is not recommended to open a package or to remove a package from a roll.
Quality Control	
Traceability (2)	Lot no. marked on the back side of the roll and on the small sticker on the roll
Defects marked by label (2)	Maximum 3 point defects / 50 m roll (2)
Each defect is balanced by	Adding 50 cm / defect (2)
Product is carefully checked before leaving the factory but should also be checked just before applying. Any claim should be accompanied with roll sticker and a sample featuring the defect.	

- (1) Other dimensions or features on request
 (2) Details are described in CAS 0337

Technical Data Sheet

Properties

- Tear resistant
- High tensile strength
- Fire resistant
- Easy re-paintable
- Breathable
- PVC-free



Edited by:
ADFORS Construction Products Europe

SAINT-GOBAIN ADFORS CZ s.r.o.
 Sokolovska 106
 CZ - 570 21 Litomyšl
 Tel: +420 461 651 111
 Fax: +420 461 612 769
www.adfors.com

ADFORS Construction Products Europe reserves the right to change the information given herein without prior notice.

Last update: 23/11/2015